



AIGI HIGH QUALITY PACKINGS

Super Severe Slurry Packing

DATA SHEET



Properties Value

Color	Black/Grey
Temperature	260°C (500 F)
PH Range	PH 0-13
Max. Liner speed	18 m/s (3600 Ft/ min)
Pressure	28 Kg/cm ² (400 PSI / 28 Bar)

Service Media & Conditions

Ash Slurry, Mineral Slurry, Bauxite Slurry, Bottom Ash Slurry, Fly Ash, Dirty water and other aggressive slurry applications

Application

Wide range for slurry sealing applications: Pumps, mixers, refiners, Valves, Agitators and other rotating equipment.

SSSP comes in all cross-sections (size) and 5 pound and 10 pound boxes



SSSP is braided using a mix of high carbon content carbon fibers and PTFE yarn and then finish lubricated with high quality graphite. The high temperature resistance strength, self-lubricating properties of high carbon fiber combined with the flexibility, chemical resistance and stuffing box conformability of PTFE fibers makes SSSP the optimal choice for slurry applications in industries such as mining, pulp and paper, metals processing and **Power Stations**



AIGI ENVIRONMENTAL INCORPORATED

A Subsidiary of AIGI Group

www.aigienvironmental.com



You Tube

To visit our channel go to :
<http://youtube.com/Aigienvironmental1996>

Distributed by :

Sizonke Trading
Quality Engineering Solutions & Supplies
Web: www.sizonkegroup.co.za