

TECHNICAL DATA SHEET

AVKOPACK® 1208



CHARACTERISTICS

Gland packing with guaranteed quality manufactured from high technology raw materials and yarns using up-to-dated production technology. AVKOPACK® 1208 is braided from blend of stainless steel yarn and aramide yarn

Application

AVKOPACK® 1208 is used in glass industry for insulation of tongues, clutches, vacuum hands, moulds, automatic production lines, etc.

Advantages

The main material used for the production of this packing blend of staple aramide fibers and stainless steel fibers. Main advantage is high temperature resistance and abrasive resistance. This packing guarantees long exploitation term and keeps the environment from being polluted.

Technical parameters

Working temperature: Up to 700°C Density 0,95 g/cm³

Standard dimensions: Dia 6, dia 8, dia 10, 6x6, 8x8, 10x10, 14x9, 15x11

Quality Control

The whole production process is supervised in accordance with the Quality System ISO 9001, ISO 14001, OHSAS 18001.

Human hazardous

Not registered.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO® JSC is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.

Czech Republic, Tuchorazská 1433/17, Cesky Brod 282 01, Tel./Fax: 00420 321 622 657,

Mobile: 00420 774 164 120, e-mail: office@avko.eu; web: www.avko.eu ISO 9001, ISO 14001, OHSAS 18001